



Straight Bar

The **Straight Bar** provides a means of extending the toolstring while maintaining the maximum through bore. The tubular section between the top and bottom sub can be interchanged to vary the length of the Straight Bar, offering an ideal solution to spacing out tools within the toolstring without compromising the flow requirements of flow-activated or jetting tools.

Features

- 1) Full flow through bore
- 2) Solid construction



Straight Bar				
Size	O.D.	I.D.	Connection	Length
1-11/16"	1.687"	0.750"	1" AMMT	2ft, 3ft, 4ft, 5ft
1-3/4"	1.750"	0.750"	1" AMMT	2ft, 3ft, 4ft, 5ft
2"	2.000"	1.000"	1-1/2" AMMT	2ft, 3ft, 4ft, 5ft
2-1/8"	2.125"	1.000"	1-1/2" AMMT	2ft, 3ft, 4ft, 5ft
2-1/4"	2.250"	1.000"	1-1/2" AMMT	2ft, 3ft, 4ft, 5ft
2-3/8"	2.375"	1.000"	1-1/2" AMMT	2ft, 3ft, 4ft, 5ft
2-7/8"	2.875"	1.250"	2-3/8" PAC	2ft, 3ft, 4ft, 5ft
3-1/8"	3.125"	1.250"	2-3/8" PAC	2ft, 3ft, 4ft, 5ft

- 1) Other sizes available on request.
- 2) AMMT, PAC and other thread connection for selective.
- 3) STD and H₂S service environment for selective. Quote with STD service if no specify.

Subject to change without notice