



## Fluted Centralizer

The **Fluted Centralizer** is designed to be included as part of the coiled tubing work string to assist in providing centralization to allow easier location of tools during fishing or to provide general stability in the tubing. The Fluted Centralizer has a full flow through bore, allowing the passage of darts or drop balls, and is available in a specific length. The Fluted Centralizers are available in all common sizes.



### Features

- 1) Full flow through bore
- 2) Solid one-piece construction

Fluted Centralizer			
Max. O.D.	I.D.	Tensile Strength	Connection
2.00"	0.75"	46000lbs	1" AMMT
2.25"	0.75"	48000lbs	1" AMMT
2.62"	0.87"	78000lbs	1-1/2" AMMT
2.75"	1.00"	78000lbs	1-1/2" AMMT
3.00"	1.00"	78000lbs	1-1/2" AMMT
3.50"	1.00"	80000lbs	2-3/8" PAC
4.00"	1.00"	80000lbs	2-3/8" PAC
4.25"	1.00"	100000lbs	2-3/8" PAC
4.50"	1.25"	100000lbs	2-3/8" PAC

- 1) *Other sizes available on request.*
- 2) *AMMT, PAC and other thread connection for selective.*
- 3) *STD and H<sub>2</sub>S service environment for selective. Quote with STD service if no specify.*

*Subject to change without notice*