



# Side Door Stripper Packer

The **Side Door Stripper Packer** is normally designed to install between the Coiled Tubing Injection Head and the Quad Ram BOP. It is used dynamic seal the wellhead when the coiled tubing is in lifting and lowering operation so as to prevent blowout accidents.

Side Door Stripper Packer main consists of top hydraulic cylinder, bushing assy, top piston, bottom piton, bottom hydraulic cylinder, side door and other parts. There are Quick Union and Flange type for selective of the Side Door Stripper Packer bottom connection. It could connect with the Quad Ram BOP directly, or between them the Lubricators and Bleed-off Sub can be added too.

The Side Door Stripper could allow replace the Packer Rubber and Bushing from the side door though the tubing in the well.

### Feature

- 1) Safety and easy maintenance.
- 2) Allow replace Packer Rubber and Bushing in operation.
- 3) Bottom Quick Union and Flange connection for selective.

# Main Parameter

- 1) Working Pressure
- 2) Coiled tubing Size you applied
- 3) Upper and Lower Connection required
- 4) Service Environment (STD or H2S)
- 5) Working Temperature





Honest Professional Reliable Cost-effective





10000psi Side Door Stripper Packer						
Model	Working Pressure	CT Size	Qty. Of Packing Rubber	Bottom Connection	Service	Working Temperature
FPH6-70	10000Psi	- 1"~2-7/8"	1	CB24 or API 2 9/16"-10K ( BX153) Open Flange	STD or H2S	P + U -20°F~+250°F (-29°C~+121°C) Or As Required
2FPH6-70	10000Psi		2	CB24 or API 2 9/16"-10K ( BX153) Open Flange		
FPH7-70	10000Psi		1	CB34 or API 3 1/16"-10K ( BX154) Open Flange		
2FPH7-70	10000Psi		2	CB34 or API 3 1/16"-10K ( BX154) Open Flange		
FPH10-70	10000Psi		1	CB44 or API 4 1/16"-10K ( BX155) Open Flange		
2FPH10-70	10000Psi		2	CB44 or API 4 1/16"-10K ( BX155) Open Flange		
FPH13-70	10000Psi		1	CO54 or API 5 1/8"-10K ( BX169) Open Flange		
2FPH13-70	10000Psi		2	CO54 or API 5 1/8"-10K ( BX169) Open Flange		

#### Note

- 1) Additional size available on request.
- 2) There are Bowen (Type B), Otis (Type O) for Quick Union selective.

### Normal Guarantee Period

12 months after the clients received the Equipment

or 13 months after the commodity be shipped from Chinese Harbor.

## **Information Required When Inquiry**

If you will purchase the whole Coiled Tubing PCE,

please refer to the *Information Required When Inquiry* in Chapter 《Coiled Tubing PCE》.

If you purchase the Side Door Stripper Packer separately,

the Main Parameter information above mentioned will be asked.

Subject to change without notice

Honest Professional Reliable Cost-effective