



Sand Pump Bailer

Sand Pump Bailer is a wireline service tool used to clear debris which has settled on top of the subsurface equipment preventing recovery of the equipment by regular wireline operations. The Sand Pump Bailer is a pump type tool which operates on the conventional lift pump and piston principle.

A double male adapter sub and extension bailer tube are available as optional extras in the event of large volume bailing operations.

Please specify Bailer Shoe sizes and configuration when ordering.

- 1) Flat Bottom: for easy bailing of sand
- 2) Angled Bottom: for bailing hard packed sand
- 3) Flapper Bottom: for bailing metallic particles which can not pass thru ball & seat

Sand Pump Bailers			
Size (in.)	Actual. OD (in.)	F/N OD (in.)	Top Connection (in. TPI)
1-1/2	1.50	1.375	15/16-10 UN
1-3/4	1.75	1.375	15/16-10 UN
2	2.00	1.75	1-1/16-10 UN
2-1/2	2.50	2.313	1-1/16-10 UN
3	3.00	2.313	1-1/16-10 UN
3-1/2	3.50	2.313	1-9/16-10 UN
4	4.00	2.313	1-9/16-10 UN

Other sizes available on request.



Sand Pump Bailer

Note : Please specify information below when inquiry

- 1) Tool Size
- 2) Bailer shoe type required
- 3) Connection type

Subject to change without notice