



## Risers / Lubricators

**Riser/Lubricator** is used to safely contain the tool string under pressure while entering the well or exiting the well. Lubricator sections are configured to provide overall length, sufficient enough to accommodate the required tool string configuration.

Integral Union, threaded Union or Flange connections are available. The union connection incorporates a seal to keep moisture out of the threads on the back-side of the union to prevent corrosion and allow for easier servicing.

Risers/Lubricators are available in customer specified lengths, sizes and working pressures.



### Feature

- 1) One piece forged Pipe Body.
- 2) Assemblies available in custom lengths and sizes.
- 3) Available with customized top and bottom connections.
- 4) Working pressure and service ratings available.
- 5) Industry-standard unions.

### Main Parameter

- 1) I.D.
- 2) Working Pressure
- 3) Upper and Lower Union Required  
( Bowen or Otis or Flange )
- 4) Service Environment ( STD or H2S )
- 5) Working Temperature





Riser / Lubricator						
Model	Working Pressure	Normal I.D.	Connection Type	Upper and Lower Connection	Service	Working Temperature
FPG6-70	10000Psi	2-9/16"	Integral Union, Threaded Union, Flange	CB24 or API 2 9/16"-10K ( BX153) Flange	STD or H2S	P + U -20°F~+250°F (-29°C~+121°C) Or As Required
FPG7-70	10000Psi	3-1/16"		CB34 or API 3 1/16"-10K ( BX154) Flange		
FPG7-105	15000Psi			CO36 or API 3 1/16"-15K ( BX154) Flange		
FPG10-70	10000Psi	4-1/16"		CB44 or API 4 1/16"-10K ( BX155) Flange		
FPG10-105	15000Psi			CO46 or API 4 1/16"-15K ( BX155) Flange		
FPG13-70	10000Psi	5-1/8"		CO54 or API 5 1/8"-10K ( BX169) Flange		
FPG13-105	15000Psi			CO56 or API 5 1/8"-15K ( BX169) Flange		

*Note: 4ft, 8ft, 10ft length are normal Lubricator length for selective. Customized length available on request.*

**Note**

- 1) There are Bowen (Type B), Otis (Type O) for Quick Union selective.
- 2) Additional size available on request.





### ***Normal Guarantee Period***

12 months after the clients received the Equipment  
or 13 months after the commodity be shipped from Chinese Harbor.

### ***Information Required When Inquiry***

If you will purchase the whole Coiled Tubing PCE,  
please refer to the [Information Required When Inquiry](#) in Chapter 《Coiled Tubing PCE》 .  
If you purchase the Riser/Lubricator separately,  
the ***Main Parameter*** information above mentioned will be asked.

*Subject to change without notice*