



Tubular Jar

Tubular Jars are used in Tool String for effective jarring. Tubular Jars are commonly used to remove obstacles from the tubing ID by jarring.

This is an effective tool during fishing of wire as possibility of Tubular Jar getting jammed with wire is minimal.

This type of Jar is used mostly when jarring in debris and other foreign matter that may be in the tubing. The Jar is tubular in construction, and the tube section is perforated for fluid bypass, to facilitate plunger movement.

Tubular Jars				
Size	Actual. OD	F/N OD	Connection	Stoke
(in.)	(in.)	(in.)	(in. TPI)	(in.)
1	1.000	0.875	5/8-11 UN	18
1-1/4	1.250	1.187	15/16-10 UN	20
1-1/4	1.250	1.187	15/16-10 UN	24
1-1/4	1.250	1.187	15/16-10 UN	30
1-1/2	1.500	1.375	15/16-10 UN	20
1-1/2	1.500	1.375	15/16-10 UN	24
1-1/2	1.500	1.375	15/16-10 UN	30
1-3/4	1.750	1.375	15/16-10 UN	20
1-3/4	1.750	1.375	15/16-10 UN	30
1-7/8	1.875	1.750	1-1/16-10 UN	20
1-7/8	1.875	1.750	1-1/16-10 UN	30
2-1/8	2.125	1.750	1-1/16-10 UN	20
2-1/8	2.125	1.750	1-1/16-10 UN	24
2-1/8	2.125	1.750	1-1/16-10 UN	30
2-1/2	2.500	2.312	1-9/16-10 UN	24
2-1/2	2.500	2.312	1-9/16-10 UN	30

Other sizes available on request.



Tubular Jar

Note: Please specify information below when inquiry

- 1) Tool Size
- 2) Stroke required
- 3) Connection type

Subject to change without notice